



Real-Time IoT Data Processing with Oracle GoldenGate and Cloud Storage Integration

Raghu Murthy Shankeshi

Abstract: Real-time data processing frameworks must efficiently handle massive data flows because the rapid technology growth of Internet of Things devices demands such frameworks. The time-sensitive limitations of IoT applications render traditional batch-processing methods unusable because of the introduction of processing delays. The complete work examines the utilization of Oracle GoldenGate together with cloud storage as a solution to provide real-time data replication benefits which combine high performance and scalability. The system developed a framework with Oracle GoldenGate for fast data conversion and cloud-based storage that enabled scale retention capabilities. Testing of the framework involved measurements for latency, throughput, scalability, and fault tolerance. Under high workload scenarios, the system experienced a maximum of 10.2 ms of latency yet it persisted an average latency of 6.2 ms. The system processed data at a rate of 15,500 events per second which enables its operation with large-scale IoT data streams. Testing results showed a maximum performance depletion of 15% when the IoT device base expanded. The fault tolerance evaluations of the system showed an average failure recovery duration of 2.5 seconds which ensured essential system reliability. This research evidence proves that Oracle GoldenGate surpasses batch processing when handling real-time IoT data. Future deployment of the solution demands resolving cloud storage dependency together with cost constraints and security risks. Researchers will examine edge computing implementations as a future study to improve latency performance along with replication performance. The research delivers essential knowledge to IoT developers and cloud services providers who need high-scalability real-time data processing systems.

Keywords: Internet Of Things (IoTs), Real-Time Processing, Oracle Goldengate, Cloud Storage, Scalability, Latency, Fault Tolerance.

INTRODUCTION

The quick rise of Internet of Things (IoT) devices changed the patterns of data production along with processing techniques and industrial applications. IoT systems serve as essential components in healthcare facilities along with manufacturing setups and autonomous vehicles in addition to their role in smart city operations during. Hot IoT devices produce massive data streams that demand reliable technological systems that perform time-sensitive data operations alongside scalability features. The rapid growth of IoT data has brought new complexities to maintaining data integration and processing capabilities because of the growing IoT ecosystem intricacy. Time-sensitive processing of IoT data faces the major challenge of achieving fast replication and transformation while maintaining data stability. The dependence on batch processing in traditional approaches leads to delayed operations that block their practical use within time-demands of IoT platforms. Real-time replication tools like Oracle GoldenGate create solutions to handle data challenges by establishing high-speed data transfers which work across different systems. The implementation of cloud storage systems represents a decisive aspect for IoT environments to achieve scalability functions and improved data accessibility. Data from IoT applications finds secure storage and accessible analysis through distributed systems offered by platforms such as Amazon S3 and Google Cloud Storage which work from any location. Using real-time data replication tools such as Oracle GoldenGate with cloud storage requires the resolution of three primary challenges which include data consistency maintenance and resource optimization together with latency minimum requirements. The present work studies the implementation process that combines Oracle GoldenGate with cloud storage for real-time IoT data processing to solve issues related to latency, scalability, and fault tolerance requirements. A framework to optimize IoT data workflows was developed through the combination of Oracle GoldenGate replication technology together with cloud storage features. A systematic evaluation of the proposed system architecture along with performance measurements involving latency throughput and scalability characteristics occurs in the study. The research fills an important knowledge gap through its practical approach to developing solutions for IoT systems. The research outcomes from this study will benefit IoT system designers and cloud service providers by enabling them to develop scalable efficient reliable real-time data processing systems.

The quick rise of Internet of Things (IoT) devices changed the patterns of data production along with processing techniques and industrial applications. IoT systems serve as essential components in healthcare facilities along with manufacturing setups and autonomous vehicles in addition to their role in smart city operations during. Hot IoT devices produce massive data streams that demand reliable technological systems that perform time-sensitive data operations alongside scalability features. The rapid growth of IoT data has brought new complexities to maintaining data integration and processing capabilities because of the growing IoT ecosystem intricacy. Time-sensitive processing of IoT data faces the major challenge of achieving fast replication and transformation while maintaining data stability. The dependence on batch processing in traditional approaches leads to delayed operations that block their practical use within time-demands of IoT platforms. Real-time replication tools like Oracle GoldenGate create solutions to handle data challenges by establishing high-speed data transfers which work across different systems. The implementation of cloud storage systems represents a decisive aspect for IoT environments to achieve scalability functions and improved data accessibility. Data from IoT applications finds secure storage and accessible analysis through distributed systems offered by platforms such as Amazon S3 and Google Cloud Storage which work from any location. Using real-time data replication tools such as Oracle GoldenGate with cloud storage requires the resolution of three primary challenges which include data consistency maintenance and resource optimization together with latency minimum requirements. The present work studies the implementation process that combines Oracle GoldenGate with cloud storage for real-time IoT data processing to solve issues related to latency, scalability, and fault tolerance requirements. A framework to optimize IoT data workflows was developed through the combination of Oracle GoldenGate replication technology together with cloud storage features. A systematic evaluation of the proposed system architecture along with performance measurements involving latency throughput and scalability characteristics occurs in the study. The research fills an important knowledge gap through its practical approach to developing solutions for IoT systems. The research outcomes from this study will benefit IoT system designers and cloud service providers by enabling them to develop scalable efficient reliable real-time data processing systems.




Fig 1: Optimizing IoT Data Processing

METHODOLOGY

This section explains the framework design for IoT data processing in real-time by implementing Oracle GoldenGate with cloud storage systems. The methodology depends on developing scalable designs and implementing data workflows in real time and performing system performance evaluations with specific key metrics.

1. Proposed Architecture

The system architecture incorporates real-time replication features of Oracle GoldenGate together with cloud storage distribution capabilities. This system processes extensive IoT data flows resulting from different devices through its designed infrastructure which enables trouble-free operations and storage capabilities. The core components include:

1.1. IoT Data Sources: A network of IoT devices generating continuous data streams, such as sensor readings or event logs.

1.2. Oracle GoldenGate: Oracle GoldenGate functions as middleware to perform quick real-time conversion of IoT data and maintains high data reliability with low latency.

1.3. Cloud Storage: Platforms such as Amazon S3 or Google Cloud Storage serve as the repository for processed data, enabling easy access and analysis.

1.4. The Analytics Layer functions as an optional element which conducts predictive analytics work or machine learning processing and other complex data handling procedures.

2. Workflow Description

The workflow design follows the following sequential actions:

2.1. Data Collection: IoT devices transmit raw data to an edge processing unit.

2.2. Real-time duplication: Oracle GoldenGate conducts real-time data duplication that both transforms data and stores it within a target cloud storage environment.

2.3. Cloud Storage Integration: After applying transformations to the data it gets stored in the cloud storage system for both current access and subsequent processing activities.

2.4. Data analysis: The data undergoes optional cloud-based processing using advanced analytics tools as well as AI models.

This workflow has been designed to enhance the processing speed and scalability features that combine Oracle GoldenGate with cloud storage solutions.

3. Performance Metrics

The proposed system's performance assessment relies on these identified metrics for evaluation of its efficiency:

3.1. Latency: Data replication and storage duration make up the latency performance metric.

3.2. Throughput: The system processes data at a rate of throughput per second.

3.3. Scalability: The system demonstrates its ability to scale up to handle escalating IoT devices and device data streams efficiently and effectively.

3.4. Fault Tolerance: The system demonstrates a capability to automatically recover from system breakdowns while maintaining complete data consistency.

4. Experimental Setup

The testing process started with the deployment of Oracle GoldenGate to a high-speed server which monitored a simulated IoT system. The IoT environment presented 1,000 devices which transmitted data at different rates to replicate actual IoT conditions. The system used Amazon S3 as cloud storage solution because of its ability to scale and extensive popularity.




Fig 2: IoT Data Processing Framework

Table 2: Real-Time IoT Data Processing Methodology

Methodology Aspect	Implementation Details
IoT Data Sources	Allowing continuous data transmission from 1,000 IoT devices operating at different speeds between 100 to 500 devices to replicate real-time usage conditions.
Data Replication (Oracle GoldenGate)	Implementation of Oracle GoldenGate enables real-time data replication while it captures and transmits IoT data with reduced delay times.
Cloud Storage Integration	Real-time access becomes possible through stored transformed data located in Amazon S3 infrastructure.
Performance Metrics Measured	<ul style="list-style-type: none"> - latency: The process to store data into the cloud takes the time. - Throughput: Both Events processed per second and represent measurement units for the test.
Experimental Setup	<ul style="list-style-type: none"> - 1,000 IoT devices simulated. - Oracle GoldenGate deployed on a high-speed server. - Data transmitted to Amazon S3. - Tests conducted for device loads of 100 to 500.

RESULTS

The research presents experimental results concerning the real-time IoT data processing framework regarding latency performance and throughput capabilities as well as scalability features and fault tolerant behavior. The research reveals efficient methods to connect Oracle GoldenGate with cloud storage solutions for IoT application requirements.

1. Latency Analysis

Real-time IoT data processing depends strongly on how fast data transmission occurs. The testing environment consisted of different operational levels that included IoT device numbers between 100 and 500. Figure 3 shows that the system-predicted and actual latency data points matched up due to their effective performance in sustaining low latency during increasing data throughput. System performance consisted of a 6.2 ms average latency and reached maximum results of 10.2 ms under high workload conditions.

2. Throughput Performance

The capacity to process data volume occurs as described by Throughput measurements that report data speeds in seconds. During normal workload conditions, the system established consistent event throughput by processing 12000 events per second. Under peak operating conditions Oracle GoldenGate achieved 15,500 events per second thus displaying its capability to process elevated data entry rates.

Table 2: Throughput measurements across different workloads:

Number of IoT Devices	Average Throughput (events/sec)	Peak Throughput (events/sec)
100	9,500	10,800
200	10,200	12,000
300	11,500	13,200
400	12,000	14,000
500	12,800	15,500




Fig 3: Throughput Performance Comparison

3. Scalability Evaluation

The evaluation of system scalability included testing the system under increasing amounts of IoT devices. The performance evaluation revealed that Oracle GoldenGate operated continuously with no discernible decrease during rising workload levels. Figure 4 demonstrates that system response time rises linearly as the number of IoT devices increases but maintains an overhead increase at the upper level that amounts to just 15 percent.




Fig 4. Scalability Evaluation

4. Fault Tolerance and Recovery Time

The recovery framework of the system underwent testing through simulated network failures combined with database errors. A typical failure recovery process took 2.5 seconds which confirmed the fault tolerance reliability of Oracle GoldenGate operational systems. The data replication system maintained 98.7% transaction success with no data loss to guarantee dependable data reliability.

5. Key Findings

- i. The system successfully upheld latency below 10.2 ms throughout all stages of high workload conditions.
- ii. The system maintained a stable focus on throughputs by achieving 15,500 events per second as its top performance mark.
- iii. The framework demonstrated high scalability characteristics when tested at full capacity because it caused a maximum 15 percent performance reduction.
- iv. The fault tolerance tests executed an average recovery time of 2.5 seconds to protect the system from downtime incidents.

DISCUSSION

The research results indicate that Oracle GoldenGate achieves effectiveness when paired with cloud storage for immediate IoT data processing. This part analyzes the study findings and relates them to previous research along with a discussion about the advantages and limitations of the proposed system structure.

1. Latency and Throughput Performance

At maximum workload, the system achieved an average processing delay of 6.2 ms keeping peak latency at 10.2 ms. The system demonstrates performance that fulfills industrial requirements regarding real-time IoT application needs. The performance of Oracle GoldenGate exceeded traditional database replication methods when dealing with fast IoT data streams because it prevented noticeable delays.

Analysis of system throughput demonstrated the capability to process 15,500 events each second when running at maximum performance levels thus reflecting the beneficial design characteristics of the architecture. The fast data transfer speeds allow Oracle GoldenGate to function effectively in systems that demand immediate analytical and reaction-based solutions...

2. Scalability and System Efficiency

The system data shows in Figure 4 that it achieved near-linear scalability which caused a performance decline of only 15% when handling maximum workload. The minimal performance degradation indicates that Oracle GoldenGate functions effectively to accommodate rising levels of IoT data which makes it a suitable option for extensive IoT implementations.

GoldenGate achieves higher efficiency through real-time change data capture (CDC) capabilities which replicates modified data only to reduce data processing expenses. The system performs efficiently while sustaining peak operational speed through a protocol that cuts down bandwidth usage on the network.

3. Fault Tolerance

The fault tolerance experiments confirmed that Oracle GoldenGate required on average 2.5 seconds to recover from failures while preserving system availability. The reliability of the system's failover mechanisms becomes clear through the successful replication of 98.7% of transactions without any loss of data.

Oracle GoldenGate provides an exceptional level of fault tolerance that suits its use in critical IoT environments such as industrial automation systems and smart healthcare solutions which require both high data integrity and system availability.

4. Comparing Existing Solutions

The real-time data replication capability of Oracle GoldenGate surpasses conventional batch-based IoT data storage methods in multiple ways due to its advantages.

- i. Data replication through GoldenGate occurs in real time whereas traditional batch-processing delays the accessibility of data.
- ii. GoldenGate exhibits superior capability in scaling operation since it handles distributed configurations and performs seamless cloud storage operations.
- iii. GoldenGate automates the failover process to guarantee fault recovery while traditional systems need manual intervention.

5. Future Consideration

A few disadvantages exist in the proposed framework design despite its benefits.

5.1. Cloud Storage Dependency: The system depends on stable cloud storage processes as well as functioning network capability to deliver required performance. The occurrence of network disruptions demands quick temporary data buffering to stop information loss.

5.2. Barriers Of Cost: The high performance of Oracle GoldenGate encounters cost barriers for small-scale IoT deployments because of its licensing expenses.

5.3. Security Challenges: Security challenges emerge from real-time replication because it needs constant data transfer that requires advanced access controls and security encryption to block unauthorized access.

Studies need to concentrate on developing edge computing integration procedures to improve latency reduction alongside system resilience elevation. GoldenGate's replication filters should receive optimization because this will reduce unnecessary data transfer which improves system performance.

CONCLUSION

Researchers have proven that Oracle GoldenGate technology works effectively with cloud storage solutions for processing IoT data in real time. The research findings present vital technical indicators comprising quick data replication services as well as high-speed performance and flexible growth and reliable failure protection.

Under excessive workload conditions, the system maintained a latency level of 6.2 ms which peaked at 10.2 ms thus providing quick response times for real-time IoT applications. The implemented system demonstrated high efficiency by processing 15,500 events instantly each second. The scalability tests revealed that Oracle GoldenGate systems maintained consistent performance throughout the increase in IoT devices since their maximum overhead remained at 15%. The failure recovery tests showed that the system achieved an average restoration period of 2.5 seconds which guaranteed both high data availability and integrity.

The implemented system delivers multiple advantages against conventional batch processing with its protected failover functions its high scalability capabilities and reduced processing delays. The set of benefits from Oracle GoldenGate qualifies it as an appropriate choice for essential IoT applications that need real-time replication together with analytics capabilities. The deployment of this framework in real-world situations requires attention to specific constraints that include cloud storage dependency together with costs and security issues that need resolution.

Research about edge computing implementation would help extend future studies to minimize latency while enhancing distributed IoT system resilience. The performance of the data management system could be improved through optimized replication filtering approaches to reduce unnecessary data transfer operations. The development of IoT relies on Oracle GoldenGate and similar real-time data processing frameworks to provide future applications with scalable efficient and dependable data management capabilities.

REFERENCES

- [1] S. Preda, S.-V. Oprea, A. Bâra, and A. Belciu (Velicanu), "PV Forecasting Using Support Vector M.L in a Big Data Analytics Context," *Symmetry*, vol. 10, no. 12, p. 748, Dec. 2018, doi: <https://doi.org/10.3390/sym10120748>
- [2] Z. Baranowski, M. Grzybek, L. Canali, D. L. Garcia, and K. Surdy, "Scale out databases for CERN use cases," *Journal of Physics: Conference Series*, vol. 664, no. 4, p. 042002, Dec. 2015, doi: <https://doi.org/10.1088/1742-6596/664/4/042002>
- [3] G. Harrison, "Database of the Future," *Apress, Berkeley, CA.*, Jan. 2015, doi: https://doi.org/10.1007/978-1-4842-1329-2_12
- [4] G. Gingras, M. Adda, A. Bouzouane, H. Ibrahim, and C. Dallaire, "IoT Ambient Assisted Living: Scalable Analytics Architecture and Flexible Process," *Procedia Computer Science*, vol. 177, pp. 396–404, 2020, doi: <https://doi.org/10.1016/j.procs.2020.10.053>
- [5] M. Parto, C. Saldana, and T. Kurfess, "Real-Time Outlier Detection and Bayesian Classification using Incremental Computations for Efficient and Scalable Stream Analytics for IoT for Manufacturing," *Procedia Manufacturing*, vol. 48, pp. 968–979, 2020, doi: <https://doi.org/10.1016/j.promfg.2020.05.136>
- [6] H. Cui, X. Yi, and S. Nepal, "Achieving Scalable Access Control Over Encrypted Data for Edge Computing Networks," *IEEE Access*, vol. 6, pp. 30049–30059, 2018, doi: <https://doi.org/10.1109/access.2018.2844373>
- [7] M. Doan, V. Tran, H. Huynh, and H. Huynh, "A Scalable IoT Video Data Analytics for Smart Cities," *EAI Endorsed Transactions on Context-aware Systems and Applications*, vol. 6, no. 19, p. 163136, Nov. 2019, doi: <https://doi.org/10.4108/eai.13-7-2018.163136>
- [8] S. Misra, A. Mukherjee, A. Roy, N. Saurabh, Y. Rahulamathava, and M. Rajarajan, "Blockchain at the Edge: Performance of Resource-Constrained IoT Networks," *IEEE Transactions on Parallel and Distributed Systems*, pp. 1–1, 2020, doi: <https://doi.org/10.1109/tpds.2020.3013892>
- [9] Y. Mao, C. You, J. Zhang, K. Huang, and K. B. Letaief, "A Survey on Mobile Edge Comput.: The Commu. Perspective," *IEEE Communications Surveys Tutorials*, vol. 19, no. 4, pp. 2322–2358, 2017, doi: <https://doi.org/10.1109/COMST.2017.2745201>
- [10] E. Sisinni, A. Saifullah, S. Han, U. Jennehag, and M. Gidlund, "Industrial Internet of Things: Challenges, Opportunities, and Directions," *IEEE Transactions on Industrial Informatics*, vol. 14, no. 11, pp. 4724–4734, Nov. 2018, doi: <https://doi.org/10.1109/tii.2018.2852491>
- [11] S. Sicari, A. Rizzardi, L. A. Grieco, and A. Coen-Porisini, "Security, privacy and trust in Internet of Things: The road ahead," *Computer Networks*, vol. 76, no. 1, pp. 146–164, Jan. 2015, doi: <https://doi.org/10.1016/j.comnet.2014.11.008>
- [12] J. Yli-Huumo, D. Ko, S. Choi, S. Park, and K. Smolander, "Where Is Current Research on Blockchain Technology?—A Systematic Review," *PLOS ONE*, vol. 11, no. 10, p. e0163477, Oct. 2016, doi: <https://doi.org/10.1371/journal.pone.0163477>
- [13] F. Adelantado, X. Vilajosana, P. Tuset-Peiro, B. Martinez, J. Melia-Segui, and T. Watteyne, "Understanding the Limits of LoRaWAN," *IEEE Communications Magazine*, vol. 55, no. 9, pp. 34–40, 2017, doi: <https://doi.org/10.1109/mcom.2017.1600613>
- [14] M. R. Palattella *et al.*, "Internet of Things in the 5G Era: Enablers, Architect., and Bus. Models," *IEEE Journal on Selected Areas in Communications*, vol. 34, no. 3, pp. 510–527, Mar. 2016, doi: <https://doi.org/10.1109/jsac.2016.2525418>
- [15] M. Wollschlaeger, T. Sauter, and J. Jasperneite, "The Future of Industrial Communication: Automation Networks in the Era of the IoTs and Industry 4.0," *IEEE Industrial Electronics Magazine*, vol. 11, no. 1, pp. 17–27, Mar. 2017, doi: <https://doi.org/10.1109/mie.2017.2649104>
- [16] S. Yi, C. Li, and Q. Li, "A Survey of Fog Computing," *Proceedings of the 2015 Workshop on Mobile Big Data*, Jun. 2015, doi: <https://doi.org/10.1145/2757384.2757397>
- [17] W. Shi and S. Dustdar, "The Promise of Edge Computing," *Computer*, vol. 49, no. 5, pp. 78–81, May 2016, doi: <https://doi.org/10.1109/mc.2016.145>
- [18] Z. Zhou, X. Chen, E. Li, L. Zeng, K. Luo, and J. Zhang, "Edge Intelligence: Paving the Last Mile of Artificial Intelligence With Edge Computing," *Proceedings of the IEEE*, vol. 107, no. 8, pp. 1738–1762, Aug. 2019, doi: <https://doi.org/10.1109/jproc.2019.2918951>

[19] Y. Lu, C. Liu, K. I-Kai. Wang, H. Huang, and X. Xu, “Digital Twin-driven smart manufacturing: Connotation, reference model, applications and research issues,” *Robotics and Computer-Integrated Manufacturing*, vol. 61, no. 2, p. 101837, Feb. 2020, doi: <https://doi.org/10.1016/j.rcim.2019.101837>

[20] M. S. Hossain and G. Muhammad, “Cloud-assisted Industrial Internet of Things (IIoT) – Enabled framework for health monitoring,” *Computer Networks*, vol. 101, pp. 192–202, Jun. 2016, doi: <https://doi.org/10.1016/j.comnet.2016.01.009>

[21] M. Z. Chowdhury, Md. Shahjalal, S. Ahmed, and Y. M. Jang, “6G Wireless Communication Systems: Applications, Requirements, Technologies, Challenges, and Research Directions,” *IEEE Open Journal of the Communications Society*, vol. 1, no. 1, pp. 1–1, 2020, doi: <https://doi.org/10.1109/ojcoms.2020.3010270>

[22] T. M. Fernandez-Carames and P. Fraga-Lamas, “A Review on the Use of Blockchain for the Internet of Things,” *IEEE Access*, vol. 6, pp. 32979–33001, 2018, doi: <https://doi.org/10.1109/access.2018.2842685>

[23] M. Aazam and E.-N. Huh, “Fog Computing and Smart Gateway Based Communication for Cloud of Things,” *2014 International Conference on Future Internet of Things and Cloud*, Aug. 2014, doi: <https://doi.org/10.1109/ficloud.2014.83>

[24] M. R. Palattella *et al.*, “Standardized Protocol Stack for the Internet of (Important) Things,” *IEEE Communications Surveys & Tutorials*, vol. 15, no. 3, pp. 1389–1406, 2013, doi: <https://doi.org/10.1109/surv.2012.111412.00158>

[25] A. Rasheed, O. San, and T. Kvamsdal, “Digital Twin: Values, Challenges and Enablers From a Modeling Perspective,” *IEEE Access*, vol. 8, no. 1, pp. 21980–22012, 2020, doi: <https://doi.org/10.1109/access.2020.2970143>

[26] M. S. Ali, M. Vecchio, et al, “Applications of Blockchains in the Internet of Things: A Comprehensive Survey,” *IEEE Communications Surveys & Tutorials*, vol. 21, no. 2, pp. 1676–1717, 2019, doi: <https://doi.org/10.1109/comst.2018.2886932>

[27] Zhang, P. Patras, and H. Haddadi, “Deep Learning in Mobile and Wireless Networking: A Survey,” *IEEE Communications Surveys & Tutorials*, vol. 21, no. 3, pp. 2224–2287, 2019, doi: <https://doi.org/10.1109/comst.2019.2904897>

[28] N.Luong *et al.*, “Applicat. of Deep Reinforcement Learning in Communicat. and Networking: A Survey,” *IEEE Communicat. Surveys Tutorials*, vol. 21, no. 4, pp. 3133–3174, 2019, doi: <https://doi.org/10.1109/COMST.2019.2916583>

