



Afterburner Jet Engine

¹Aditya Divte, ²Rushikesh Ghait, ³Swapnil Gawhane, ³Prof. Kapil Mundada

Department of Instrumentation and Control Engineering
Vishwakarma Institute of Technology, Bibwewadi, Pune

Abstract: This research paper details an experimental investigation into the design, construction, and testing of a novel prototype detachable afterburner employing butane combustion. The motivation behind this study stems from the pursuit of innovative solutions to enhance the efficiency and environmental sustainability of jet engine afterburners. The prototype incorporates a fan with a 12V motor, a glow plug, and a carefully designed arrangement within an acrylic pipe to channel butane combustion. The study explores the stability of butane combustion, its impact on flame characteristics, and the potential for thrust augmentation.

Keywords—*component, formatting, style, styling, insert*

INTRODUCTION

Jet engine afterburners, also known as reheat systems, represent a crucial component in the realm of aviation propulsion, especially in military aircraft. These systems play a transformative role in enhancing the performance of jet engines, enabling high-speed flight, rapid acceleration, and improved maneuverability. The concept of an afterburner revolves around the augmentation of thrust during specific operational phases, providing a decisive edge in combat scenarios or when swift, supersonic flight is required. While afterburners confer significant advantages in terms of thrust augmentation, they also introduce challenges such as increased fuel consumption and higher emissions. Consequently, research and development in afterburner technology continually strive to optimize performance, reduce environmental impact, and address the complex engineering considerations associated with their integration into jet engines.

LITERATURE REVIEW

Afterburners, or reheat systems, are integral components in military jet engines designed to augment thrust during specific flight conditions. The combustion of additional fuel in the afterburner section increases exhaust velocity, resulting in enhanced thrust. Extensive research has focused on optimizing afterburner designs, improving combustion efficiency, and managing the associated thermal stresses (Hill & Peterson, 1992).

Despite their effectiveness, traditional afterburners pose challenges, including increased fuel consumption and environmental impact due to higher emissions. The literature emphasizes the need for innovative solutions to address these challenges and enhance overall engine efficiency (Mattingly et al., 2002).

The exploration of alternative fuels in aviation has gained traction in recent years. While many studies focus on biofuels and synthetic alternatives, research on the use of butane in afterburners is relatively limited. Alternative fuels offer the potential for reduced greenhouse gas emissions and increased energy security (Boeing, 2020).

Butane, a hydrocarbon with a relatively simple molecular structure, has characteristics that make it a promising candidate for afterburner applications. It is readily available, has a high energy density, and is known for clean combustion. The literature suggests that butane combustion could offer advantages in terms of emissions and combustion efficiency in comparison to traditional fuels (Smith, 2018).

Few studies have specifically investigated the use of butane in jet engine afterburners. Experimental studies on small-scale prototypes, such as the one proposed in this paper, are essential for assessing the feasibility and performance of butane combustion in afterburners. This gap in the literature highlights the novelty and importance of the current research endeavor.

COMPONENTS

The prototype for the detachable afterburner encompasses several key components designed for optimal performance and safety.

- Acrylic Pipe
- 775 DC Motor with Fan
- Glow Plug
- Brass Tube

A. Acrylic Pipe:

The detachable afterburner is housed within a transparent acrylic pipe, providing visibility into the combustion process. This material was chosen for its durability, heat resistance, and transparency, allowing for both structural integrity and observation of the internal processes.



Fig.1. Acrylic Pipe

B. 775 DC Motor with Fan:

A 775 DC motor, paired with a fan, serves as the primary mechanism for creating airflow within the afterburner. The fan facilitates proper air-fuel mixing and contributes to the stability of combustion by ensuring a consistent flow of gases through the system.



Fig.2. 775 DC Motor

C. Glow Plug:

The glow plug, a critical component, is employed for initiating and sustaining the combustion of butane within the afterburner. Its role is pivotal in ensuring a reliable ignition source for the fuel-air mixture. The glow provides continuous heat for the experiment to be feasible.

D. Brass Tube and Aluminum Tube:

The brass tube, carefully perforated for controlled fuel release, and the aluminum tube, which serves as a conduit for the combustion process, are integral to the design. The choice of materials considers heat resistance, weight, and structural robustness to withstand the high temperatures generated during combustion. The reason we have used a brass tube in the experiment is because it doesn't catch the spark.

MODELING AND FABRICATION



Fig.7. Afterburner Conceptual Model

The construction of the detachable afterburner involved the use of several materials and components carefully selected for their heat resistance, durability, and compatibility with butane combustion. The main components included a 4-inch diameter, 2-foot length acrylic pipe for the afterburner chamber, a high-temperature-resistant glow plug for ignition, and a fuel delivery system designed to handle butane.

A high-temperature glow plug was integrated into the afterburner chamber to facilitate reliable ignition of the butane. The glow plug was positioned at an optimal location to ensure uniform combustion within the chamber. Electrical wiring connected the glow plug to a control system for precise activation.

The fuel delivery system included a pressurized butane tank, a flow control valve, and a nozzle for controlled fuel injection into the afterburner chamber. The system was designed to provide a steady and controlled flow of butane, preventing overconsumption and ensuring a stable combustion process.

The afterburner assembly was mounted in proximity to the 755 DC motor, ensuring proper alignment for efficient exhaust gas interaction. A detachable mechanism was implemented to facilitate easy removal and reattachment for modular testing. The motor and afterburner were securely integrated using a custom mounting bracket.

Rigorous quality control measures were employed throughout the fabrication process to ensure the integrity of the afterburner system. Prior to experimentation, the system underwent a series of bench tests to verify the functionality of each component, detect any potential leaks, and assess the reliability of the ignition system.

RESULT

From the above thrust measurement test, we can conclude that as the distance between the combustion chamber and the fuel injector increases, there is an increase in the thrust value. At 30 mm distance, the thrust measured was maximum i.e., 1.3 lb. And after that it decreases gradually. Hence, an optimal fuel combustion is achieved at 30 mm distance for the combustion of butane fuel.

The rpm of the motor can provide a variable effect on the thrust generated by the afterburner. In the model constructed through trial and error, we found out the optimal speed for the motor to operate the fan, which is 6000 rpm.

APPLICATION

The detachable afterburner can find applications in experimental aerospace research for studying the impact of afterburners on thrust augmentation and exhaust characteristics. It provides a flexible platform for testing and analyzing propulsion system performance. The system can be employed as an educational tool for engineering and physics students to demonstrate principles of combustion, fluid dynamics, and propulsion. Its modular design allows students to understand the components and functionalities of afterburners in a hands-on manner. Miniature afterburners could be integrated into UAVs, providing an additional thrust boost when needed. This application could be valuable in scenarios requiring rapid acceleration or increased maneuverability for UAVs used in surveillance, reconnaissance, or emergency response.

FUTURE SCOPE

Future research can focus on refining and optimizing the combustion parameters within the afterburner. This includes investigating the ideal air-fuel mixture, ignition timing, and residence time within the combustion chamber to maximize thrust output and efficiency. Exploring alternative fuels beyond butane can be a promising avenue for research. Investigating the use of environmentally friendly and sustainable fuels could contribute to the development of afterburner systems with reduced environmental impact. Research efforts can be directed towards the exploration of advanced materials with enhanced heat resistance for the construction of afterburner components. Additionally, improving heat management strategies within the system can lead to increased durability and performance. Studying the integration of variable geometry systems within the afterburner can contribute to optimizing its performance across a range of operating conditions. Adjustable nozzles or variable geometry components could enhance the adaptability of the afterburner to different motor speeds and loads.

CONCLUSION

In conclusion, the experimental study on the prototype detachable afterburner using butane combustion represents a significant step forward in the exploration of miniature propulsion systems. The research aimed to assess the feasibility and efficiency of such a system, with a specific focus on enhancing thrust output for a 755 DC motor.

Through a carefully designed experimental setup, incorporating a 4-inch diameter, 2-foot length acrylic pipe and a glow plug for controlled butane combustion, the study yielded promising results. The afterburner demonstrated a noticeable increase in thrust when activated, indicating its potential for use in various applications, from educational demonstrations to experimental aerospace research.

REFERENCE

- [1] Zukoski, E. E., & Oates, G. C. (1985). Afterburners. *Aerothermodynamics of aircraft engine components*.
- [2] Andrikopoulos, G., & Nikolakopoulos, G. (2019). Vortex actuation via electric ducted fans: an experimental study. *Journal of Intelligent & Robotic Systems*, 95, 955-973.
- [3] Pawar, V., Kini, K., Kolge, U., Mhetre, S., & Nikhade, S. Design and Manufacturing of Mini Jet Engine.
- [4] TURKAY, M., GURGEN, S., KESKIN, G., DURMUS, S., & KUSHAN, M. C. (2019). Research on applications of mini-turbojet and turbojet engined military UAVS. *Scientific Research & Education in the Air Force-AFASES*, 2019.
- [5] Borowski, S., Dudzinski, L., Borowski, S., & Dudzinski, L. (1997). '2001: A Space Odyssey' revisited-The feasibility of 24-hour commuter flights to the moon using NTR propulsion with LUNOX afterburners. In *33rd Joint Propulsion Conference and Exhibit* (p. 2956).
- [6] Gurralla, S. R., & Shaija, A. (2021). Computational Studies on Combustion Instabilities of Afterburner for Different Equivalence Ratios.
- [7] Rajashekar, C., Shambhoo, H. S. R., Sriram, G., Kumar, S. C., Athith, G. U. S., Vijayasankaran, K., Natarajan, R., Jeyaseelan, A. R., Ashirvadam, K., & Isaac, J. J. (2020). Experimental Studies on the Thermoacoustics of Afterburner Screech Combustion Instabilities in a Model Afterburner Test Rig.
- [8] Kumar, SS, & Ganesan, V. "Flow Investigations in an Aero Gas Turbine Engine Afterburner." *Proceedings of the ASME 2005 International Mechanical Engineering Congress and Exposition*. Transportation. Orlando, Florida, USA. November 5–11, 2005. pp. 15-23. ASME.

[9] Cooper, J. and Dingle, L. (2005), "Engineering an afterburner for a miniature gas turbine engine", Aircraft Engineering and Aerospace Technology, Vol. 77 No. 2, pp. 104-108.

DongEun Lee, Seok-Min Kim, Yunsup Hwang, Young Seok Kang and Dong-Ho Rhee. "A Study of Combustion Characteristics in Afterburner for Micro Gas Turbine Engine Under Varied Fuel Supply Conditions," AIAA 2024-0104. AIAA SCITECH 2024 Forum. January 2024

